

Removable Disk Storage Array Emulating Tape Library Having Backup
and Archive Capability

Co-Inventors:

5

Name: William G. Moon
Residence: 325 W. 3300 N
Provo, Utah 84604
Citizenship: USA

10

Name: Chris Dudte
Residence: 6375 Saginaw Ct.
Sun Valley, NV 89433
Citizenship: USA

15

Name: Michael Cornwell
Residence: 101 Soquel Avenue, #402
Santa Cruz, CA 95060
Citizenship: USA

20

Name: Ronald K. Scott
Residence: 10255 East Rose Glenn Drive
Claremore, Oklahoma 74017
Citizenship: USA

25

Name: Kevin Daly
Residence: 2245 Port Carlisle
Newport Beach, CA 92660
Citizenship: USA

Field of the Invention

The present invention relates to methods and apparatus for protecting user data within a computer system. More specifically, the present invention relates to a removable rotating disk drive data storage array for
5 emulating tape library functions including backing up and archiving user data.

Background of the Invention

10 The need for effective and reliable backup and archive of user data information is well known. Considerable information system (IS) resources are devoted to providing backup and archive of information resident in computers and servers within any organization that produces and/or relies upon digital information.

15 The term "backup" means that periodically, such as each day, a backup record is made which mirrors then-present information content of computer active memory embodied as semiconductor random access memory, and/or a hard disk drive or drives, of a computer or computer
20 server. This backup operation usually, although not necessarily, involves a transfer to magnetic tape and occurs during a period of likely minimum usage of the underlying data storage resource, such as in the middle of the night. If the storage resource is thereafter lost or becomes unavailable on account of equipment failure, or for any other reason, it is then possible to
25 use the backup record to reconstruct the state of the information in storage as of the last backup time and date.

The daily backup procedure may be followed by a weekly backup procedure, a monthly backup procedure, a quarterly backup procedure, and so forth. At any point in the backup procedure, selected backup data storage media, frequently backup tape cartridges, may be physically removed from the system and relocated to a secure storage location away from the information processing/storage center. Secured backup tape cartridges then function as archival tape cartridges. One drawback of archival tape cartridges is that once they are removed to the secure storage site, they become presently unavailable to the computing system; and, depending upon conditions such as temperature, humidity, handling and storage conditions within the storage site, the tape/cartridge may deteriorate or degrade. If later needed, the archived user digital data information on the tape media of such cartridges may turn out to be unavailable.

One procedure which is used to safeguard data integrity of data on archive tape cartridges is to remove each cartridge periodically from the secure storage site, load each cartridge into a tape drive and unspool and respool the reeled tape, by carrying out an operation known as "repacking the tape pancake". During this tape-spooling operation, some or all of the archive data may be read out to determine whether such data remains intact and available as an archive. If the tape media is determined to be deteriorating, as measured by error correction activity for example, a replacement archive tape cartridge may be loaded and the archived data on the failing tape cartridge may then be transferred to the replacement cartridge. Then, the failing tape cartridge can then be discarded. Such

procedures tend to be time consuming, labor-intensive, and evidently expensive. Repeated handling and use of a tape cartridge shortens its useful life and can directly lead to its failure as a data archive resource.

5 One further drawback of tape archiving methods and technology is that drive transports are being constantly improved and upgraded technologically. It has proven very difficult to provide backwards-compatibility in tape archive systems such that more recent tape drives are able to read and recover user data from older tapes using less dense data
10 recording formats, all other considerations being the same.

One other drawback of tape archiving methods has arisen during efforts to re-use archive tapes because of less than complete erasure of overwritten data. This problem has led some users to treat tape cartridges as
15 one-use devices, greatly adding to the expense of tape archive systems operations and management. Also, because the tape cartridge is not a sealed system, external contaminants and influences may prevent a tape transport mechanism from successfully reading an archive tape. Further, tape cartridge handling equipment including tape transports, tend to be very
20 complicated electro-mechanical structures, with multiple tape path control loops and other interactive tape handling processes. If any one of these processes fails or degrades, the tape may be damaged or destroyed. Moreover, tapes written on one tape transport may not be readable on another tape transport because of accumulation of head-tape alignment
25 errors.

Tape recording has evolved since its earliest beginnings over forty years ago. Large reels of open tape have given way to small compact tape cartridges that hold increasing quantities of magnetic storage tape capable of being recorded with ever-greater information density. One form of compact single reel cartridge tape is the streaming digital linear tape system marketed by the assignee of the present invention under the DLT™ brand. The DLT system includes individual tape drives, as well as tape cartridge handling equipment and libraries. Recently, it has been proposed to create a virtual tape library by using a single DLT tape device, or several such devices within a cartridge loader environment. An example of this virtual tape library is found in commonly assigned U.S. Patent No. 6,067,481 to Saliba, entitled: "Virtual Magnetic Tape Drive Library System". An example of a cartridge loader environment is found in commonly assigned U.S. Patent No. 5,760,995 to Heller et al., entitled: "Multi-Drive, Multi-Magazine Mass Storage and Retrieval Unit for Tape Cartridges. The disclosures of U.S. Patents 6,067,481 and 5,760,995 are incorporated herein by reference thereto.

Cartridge media libraries, whether tape or optical, are well known in the art, and frequently comprise "walls of cartridges" or large cylindrical cartridge bin arrangements. A so-called "picker-gripper" mechanism (robot) operating under computer control accesses a particular cartridge bin, grips the cartridge media unit present, withdraws it from the bin, translates it to a media drive unit and causes the cartridge media unit to be loaded into the drive unit in a predetermined way. One example of an optical storage and retrieval device comprising a wall of optical media cartridges is

disclosed in U.S. Patent No. 4,675,856 to Rudy et al, entitled: "Optical Storage and Retrieval Device", the disclosure thereof being incorporated herein by reference.

5 Over the past forty years tape storage has been perceived to be a less expensive method for providing off-line storage than disk drives. While tape media alone may be somewhat less expensive than equivalent rotating hard disk drive storage, when a complex electromechanical tape drive is included, the comparison becomes more equivalent. As the rotating hard
10 disk drive storage cost-per-information-unit continues to drop, the storage industry is beginning to shift its paradigm for backup, to other storage systems, such as rotating hard disk drives.

Currently, optical and low-density magnetic media (e.g.: Iomega
15 ZIP™ drive system) are seen as alternatives to tape backup and archive. The Linear Tape Open (LTO) Consortium is offering an alternative to streaming digital linear tape (DLT).

Moreover, it has been proposed to emulate tape systems and libraries
20 with hard disk drive arrays by using a variety of technologies known as "virtual tape". Virtual tape makes disk drive resources appear as if they are sequentially accessed tape drives. By using disk drive subsystems as virtual tape devices, it is possible to stream backup data at very high data rates over a storage application network (SAN). Thus, for applications and computing
25 environments requiring higher-speed backup devices and processes, for

example on the order of 40 Mbytes per second or faster, virtual tape may provide the necessary data throughput.

Computer storage systems providers such as IBM, Sun Microsystems,
5 Storage Technology Corporation, and EMC² Corporation, offer large hard
disk drive array products which may be configured as virtual tape libraries,
but which do not exactly mirror or correspond to DLT tape backup/archive
systems. Examples of prior art virtual tape devices and systems are found
in U.S. Patent No. 4,467,421 to White, entitled: "Virtual Storage System
10 and Method"; U.S. Patent No. 5,963,971 to Fosler et al., entitled: "Method
and Apparatus for Handling Audit Requests of Logical Volumes in a Virtual
Media Server"; U.S. Patent No. 6,049,848 to Yates et al., entitled: "System
and Method for Performing High-Speed Tape Positioning Operations"; U.S.
Patent 6,070,224 to LeCrone et al., entitled: "Virtual Tape System"; U.S.
15 Patent 6,098,148 to Carlson, entitled: "Storage and Access of Data Using
Volume Trailer"; and, U.S. Patent No. 6,105,037 to Kishi, entitled:
"Apparatus for Performing Automated Reconcile Control in a Virtual Tape
System". The disclosures of these patents are incorporated herein by
reference. These prior disclosures fail to provide any teaching or suggestion
20 that the disk drives or disk drive arrays performing the virtual tape drive
emulation can be physically removed from an active data store and
relocated to a secure data archive location and then provide the archive
function typically performed by removable archive tape media.

25 Rotating hard disk drives are known to be susceptible to, and can be
damaged by, sharp shock forces incident to handling. Such forces may

cause the hard ceramic head sliders to deform the relatively soft aluminum alloy disk substrate. Accordingly, while tape storage has been emulated by disk storage, rotating hard disk drives are generally more fragile than tape cartridges from a media handling perspective.

5

Removable hard disk drive systems are known in the prior art. One example of such a system previously offered for sale by the assignee of the present invention under the "Passport™" brand is described inter alia in U.S. Patent No. 5,253,129 to Blackborow et al., entitled: "Removable and

10 Transportable Hard Disk Subsystem". That system and patent describes a hard disk drive module which was loaded into, and thereupon electrically connected with, a base housing unit, which was in turn connected electrically to a host computer via a bus structure. A hard disk drive was shock-mounted inside of a metal cartridge to provide primary resistance to
15 shock forces. A shock-resistant carrying case provided further shock resistance to the hard disk drive cartridge and enabled the cartridge to be safely transported and stored in a secure, shock-resistant environment. The Passport product found particular acceptance within the national security field where it is necessary to lock up hard disk drives containing data
20 embodying national secrets or classified information in safes and secure areas at night or during periods of inattention. An improvement in the original "Passport" removable hard disk technology is found in U.S. Patent No. 5,297,067 to Blackborow et al., entitled: "Electronic Hot Connection of Disk Drive Module to Computer Peripheral Bus". The '067 patent
25 describes methods and apparatus enabling a standard hard disk drive unit to

be "hot" connected and disconnected via a standard peripheral bus interface, such as SCSI, with an associated computing system.

An expansible fixed disk drive data storage subsystem which enables
5 attachment of a variable number of bus-level-interface hard disk drives at a single bus level logical address location is described in U.S. Patent No. 5,097,439 to Patriquin et al., entitled: "Expansible Fixed Disk Drive Subsystem for Computer", the disclosure of which is incorporated herein by reference. A rotating hard disk drive array employing redundant array of
10 individual disks (RAID) formed on hot-pluggable circuit cards is described in Statutory Invention Registration No. H1221 to Best et al., entitled: "High Speed Small Diameter Disk Storage System", the disclosure thereof being incorporated herein by reference.

15 The disclosures of U.S. Patents Nos. 5,253,129, 5,297,067, 5,097,439 and Statutory Registration H1221 fail to describe or suggest a removable multi-drive hard disk drive system for providing not only high speed backup in a real-time computing environment, but also being separately capable of being removed to a different operating environment for providing data
20 archival storage, periodic integrity checking and reduced bandwidth retrieval without any further physical relocation or handling of the particular drives and multi-drive modules.

Therefore, a hitherto unsolved need has remained for a removable
25 hard disk storage array capable of emulating tape library backup and archive

functions in a manner overcoming limitations and drawbacks of the prior art.

Objects of the Invention

5

A general object of the present invention is to provide a computer-network-attached rotating hard disk storage backup and archive system which emulates tape storage backup and archive systems and which is scalable from an entry level system to an enterprise system in a manner overcoming limitations and drawbacks of the prior art.

10

A more specific object of the present invention is to realize vastly improved tape storage backup and archive system functionality with performance, reliability and cost advantages of hard disk drive technology in a network-attached storage system.

15

Yet another specific object of the present invention is to provide a data storage backup and archive library which does not require operator intervention or robots in order to move a tape cartridge between a storage bin and a tape transport with a cartridge handler mechanism, thus overcoming limitations and drawbacks of prior tape cartridge handling solutions associated with cartridge loaders and tape libraries. In fact, one object of the present invention is to eliminate the cartridge media transport mechanism entirely.

20

25

One more specific object of the present invention is to provide a network-accessible data storage backup and archive library system in which removable magazines of hard disk drives emulate magazines of removable tape cartridges.

5

Yet another specific object of the present invention is to implement a storage system comprising a wall of multiple rotating hard disk drives in a manner analogous to a wall of tape cartridges, yet without need for separate tape drives and robotic tape cartridge handling apparatus or other externally moving parts or components.

10

One more specific object of the present invention is to provide a magazine of hard disk drives which may be installed and used in a high speed, high bandwidth data storage rack electrically coupled to a high performance computer, and which may be removed to, installed in and electrically accessed at a data archive rack monitored by a supervisory controller and connected to the high performance computer via a lower bandwidth network connection.

15

Yet another object of the present invention is to implement a unique file mark structure for implementing tape file marks within logical block address space of a hard disk drive emulating a tape cartridge.

20

These and other objects, advantages, aspects and features of the present invention will be more fully understood and appreciated upon

25

consideration of the following detailed description of preferred embodiments presented in conjunction with the accompanying drawings.

Brief Description of the Drawings

5

In the Drawings:

Figure 1 is an isometric view of a storage rack or bay for holding and connecting two seven-drive rotating hard disk unit magazines in accordance with principles of the present invention.

10

Figure 2A is an isometric view of a rack-mounted storage bay for holding and connecting two fourteen-drive rotating hard disk unit magazines in accordance with principles of the present invention.

15

Figure 2B is a highly diagrammatic, isometric view of the Figure 2A storage bay and magazines, illustrating flow of cooling air across individual drive units.

20

Figure 3A is a highly diagrammatic top plan view and block diagram of one embodiment of a multi-drive magazine of the type shown in Figure 1, illustrating a serial ATA drive interface within an active computing environment.

Figure 3B is a highly diagrammatic top plan view and block diagram showing the Figure 3A magazine within an inactive data preservation environment, in accordance with principles of the present invention.

25

Figure 4A is a highly diagrammatic top plan view and block diagram of a second embodiment of a multi-drive magazine of the type shown in Figure 1, illustrating a USB parallel bridge interface within an active computing environment.

Figure 4B is a highly diagrammatic top plan view and block diagram showing the Figure 4A magazine within an inactive data preservation environment.

Figure 5 is a highly diagrammatic top plan view and block diagram of
5 a third embodiment of a multi-drive magazine of the type shown in Figure 1, illustrating a 1394 Standard computer interface architecture.

Figure 6A is a top plan view of a multi-drive magazine of the type shown in Figure 1, illustrating shock mounting.

Figure 6B is an isometric view of a magazine foam shock mount of
10 the type employed in the Figure 6A embodiment.

Figure 7 is an electrical block diagram of a removable hard disk storage system comprising an array of multi-drive magazines for emulation of high transfer rate tape library backup functions within a central computing environment.

Figure 8 is an electrical block diagram of a removable hard disk
15 storage system of the type shown in Figure 7 wherein a SCSI bus architecture is employed within the central computing environment.

Figure 9 is an isometric view of an active hard disk data storage system comprising a series of racks holding a multiplicity of hard drive
20 magazines and showing air ventilation paths and means.

Figure 10 is an isometric view of a shock-insulated transport case for transporting up to two multi-drive magazines from the central computing environment to a secure archive environment at a remote site.

Figure 11 is an isometric view of an off-line archival storage rack
25 system for receiving a multiplicity of multi-drive hard disk magazines and for connecting each magazine to a drive monitoring system.

Figure 12 is a diagrammatic top plan view of the Figure 11 off-line archival storage rack system.

Figure 13 is a flowchart illustrating operation of the Figure 11 off-line archival storage rack system in accordance with principles of the present invention.

Figure 14 is a diagram mapping logical block address space of a hard disk drive to storage space of a tape cartridge, showing placement of double linked file mark data structures.

Figure 15 is a table illustrating structure of a file mark shown in the Figure 14 diagram.

Detailed Description of Preferred Embodiments

As noted above, hard disk drives have a number of advantages over tape cartridges for backing up and archiving computer data. Hard disk drives are fully enclosed and are generally less sensitive to changes in environmental conditions, such as temperature and humidity. Hard disk drives have data storage capacities, which closely approach storage capacities of tape cartridges. Moreover, given the susceptibility to damage incident to periodic handling and repacking of the tape pancake, tape cartridges may have average useful life less than hard disk drive units. In one aspect of the present invention, hard disk drive units are installed into multi-drive magazines. The magazines plug into active storage racks of a high speed, high bandwidth data storage array of an active computing system such as a mainframe, or a network server. The drives are operated in parallel and provide high-speed random storage and access for data files.

The drives may be kept in the active environment for a number of months or years. During the period of active disk drive usage, each of the drives will be fully tested and proven to be serviceable. Once a nominal useful life of the drives of a magazine is reached, such as 3-5 years, the magazine can be transitioned to a data archive unit. Data to be archived is then recorded onto the drives of the magazine, and it is then removed from active service, transported in a suitable shock protection carrier, and reinstalled in a drive monitoring rack in an archive location. Then, on a periodic schedule, each drive is powered up and checked in turn, to be sure that it continues to function properly and provides nominal read/write functionality. The drive's prognostics are monitored and measured against a degradation profile. If a drive is determined to be failing, then a flag is set and the magazine and drive can be removed and replaced. If the data is striped across the multiple drives of the module in a known manner, the drive monitoring system may be able to reconstruct the data of the failed drive. Alternatively, a relatively low bandwidth path may exist between the active computing system and the archive system, and the active host computer may be able to reconstruct the data from the failed drive and return it to a replacement drive installed in the magazine, or in another magazine. Also, it is practical for the host computing system to retrieve archive data from the archive system via the limited bandwidth connection, thereby eliminating any requirement that the drive/magazine be handled or transported. Further advantages and features of the present invention will become even more apparent from considering the following descriptions, which accompany the drawings.

Glossary of Terms Used

ARCHIVAL MAGAZINE: A removable shock-protected storage unit for mounting and connecting a predetermined number of self-contained rotating hard disk drive units, such as 7 or 14 such units.

- 5 DATA PRESERVATION VAULT: A system of interconnected racks for receiving and connecting archival magazines and drive units. The vault may be co-located with an active computing system, or it may be located at a different site, such as a location made to be secure from hazards such as fire, floods, earthquake, storms, etc.

- 10 ATA: An acronym for "advanced technology attachment", representing a hard disk drive industry standard interface providing 100 Megabyte per second low cost parallel interface.

BRIDGE BOARD: A printed circuit board containing electronic circuitry to interconnect between a particular hard disk drive unit and one or more
15 system interfaces.

DISK MONITORING SYSTEM: An arrangement of hardware and software for monitoring on a periodic basis all hard disk drive units of magazines installed in the Data Preservation Vault.

- IEEE 1394: An industry standard 320 Megabit per second serial small
20 computer system interface (SCSI) structure and convention.

SERIAL ATA: An industry-proposed fast serial interface for ATA interface hard disk drive units.

USB 2.0: An industry standard 480-Megabit per second universal serial bus interface structure and convention.

- 25 ACTIVE DATA STORAGE ARRAY: An on-line data storage/backup system containing one to a multiplicity of Archival Magazines.

Having in mind the foregoing, components of a removable disk storage array 10 incorporating principles of the present invention are shown in the Figure 1 depiction. Therein, a rack-mountable storage bay, or cabinet, 12 is sized to define a plurality of wells 13 and an electronic backplane circuit board 15. In the present example, left and right wells 13 are defined within cabinet 12 to receive two hard disk drive magazines 14A and 14B. In Figure 1 magazine 14A is shown removed from the left well 13, and in front of the cabinet 12, while magazine 14B is shown in the installed position fully within the right interior well 13 of the cabinet 12. Each magazine 14 has a standardized external physical layout arrangement ("form factor"), and may include such handling features, such as one or more handles 16 enabling an operator to grasp the magazine 14 in order to install it into a particular well 13 of cabinet 12. Most preferably, the act of installing a magazine 14 into a well 13 of cabinet 12 simultaneously accomplishes a task of connecting the magazine to electrical power supply and one or more computer data interface connector structure 17 which is part of or co-located with the backplane circuit board 15. Such an arrangement may be followed to facilitate "hot connection" or "hot swap" of magazines within the cabinet 12 in a manner described in U.S. Patent No. 5,297,067 or Statutory Invention Registration H1221, referred to hereinabove. The magazine bay 12 is most preferably of a standardized height and a standardized width, such as 19 inches, so that it may be installed in a conventional mainframe computer equipment rack. The bay 12 is generally open at the top and bottom, so that airflow streams may be

directed between the drives 20, e.g., from bottom to top as shown by the bold arrows of the Figure 1 example.

Each magazine 14 most preferably includes a predetermined number of hard disk drive units 20. In the Figure 1 example, each magazine 14A, 14B holds e.g., seven (7) hard disk drive units 20A, 20B, 20C, 20D, 20E, 20F, 20G. In the Figure 2A example, each magazine 14C, 14D holds e.g. up to 14 hard disk drive units 20A, 20B, 20C, 20D, 20E, 20F, 20G, 20H, 20I, 20J, 20K, 20L, 20M, and 20N. Shock-resistant formed-foam mounts 21, shown in Figure 6, are provided within each magazine 14, so that shock forces generated during normal handling of the magazine 14 during installation and removal to and from the bay 12 do not damage the delicate internal components of the hard disk drive units. Each hard disk drive unit 20 most preferably has an industry-standardized form factor, such as 3.5-inch disk diameter, half height; 2.5 inch; 1.8 inch; or 1 inch nominal disk diameter, for example. Each drive unit 20 is fully self-contained, offers specified predetermined data storage capacity and average data access time, and includes an industry-standardized interface structure and convention, such as ATA, SCSI or 1394. Ideally, each hard disk drive unit 20 provides 10 Gigabytes, or more, of data storage, and most preferably 30 Gigabytes to 200 Gigabytes or more, which equals or exceeds a contemporary data backup tape cartridge having a similar external form factor.

The hard disk drive units 20 are mounted in the magazine 14 with a slightly spaced-apart arrangement. This arrangement enables forced airflow to pass between the units and thereby cool the units 20 and backplane

circuit 15 during active use, when the units operate in parallel and generate substantial heat which must be carried off or dissipated. Standard cabling (not shown) is provided to provide power and data connections between each drive unit 20 and a connector structure of each magazine which mates
5 with the connector structure 17 of the bay 12.

As shown in Figure 3A, for example, each of the seven hard disk drive units 20A-20G is provided with a visual indicator 22A-22G, such as a light emitting diode (LED). In the Figure 3A example, the LED units 22A-
10 22G are mounted in a transverse lip of the magazine 14A above a front wall of each drive unit 20. In the Figure 2A example, the magazines 14C and 14D have front panels 23, which include the 14 visual indicator LEDs 22A-22N, corresponding to drive units 20A-20N respectively. Each LED 22
15 may be multi-colored, so that one color, such as green, is emitted when the drive unit is operating normally, and another color, such as red, is emitted to indicate a fault condition within the particular drive unit 20. An amber color may be emitted if a particular drive is failing or degrading, but has not yet failed in service. Information about a variety of operational parameters within a particular unit 20 is typically self-collected and recorded in a
20 reserved section of disk storage space and is available to be read from the unit in order to predict unit failure in accordance with conventional failure prediction methods. These measurements may be of the type described in U.S. Patent No. 6,122,131 to Jeppson, entitled: "Adaptively-controlled Disk Drive Assembly", the disclosure thereof being incorporated by
25 reference. A method for predicting early head crashes is described in U.S. Patent No. 5,410,439 to Egbert et al., entitled: "Disk File with Clearance

and Glide Measurement and Early Head Crash Warning", the disclosure thereof being incorporated herein by reference. Since standard hard disk drive units 20 no longer are equipped with activity lights, the visual indicators 22 are arranged as part of magazine 14 so as to be readily visible to an operator facing the front of the magazine 14.

As shown in Figures 1, 3A, 4A and 5, the drive units 20 are most preferably mounted together within a magazine 14 in a closely-spaced-apart side-by-side arrangement that provides an air-space 24 between adjacently facing major sidewalls of adjacent drive units 20, thereby admitting an airflow for cooling, as perhaps best shown in Figure 2B. Cooling fans 101 at the top of magazine racks 102 of an active backup storage system 100 (Figure 9) pull air from the ambient through the racks 102 and magazines 14 in order to achieve the desired cooling airflow. This provides the needed cooling of the drive units 20 when they are simultaneously operating and functioning in the active computing environment.

In the active computing environment 100 depicted in Figure 3A, the magazine 14A includes, in addition to the seven drives 20A-20G a series of internal serial buses 32 and serial connectors 34 in number equal to the number of drive units 20 present. In this present example, serial buses 32A, 32B, 32C, 32D, 32E, 32F and 32G respectively connect serial ATA interfaces of drive units 20A, 20B, 20C, 20D, 20E, 20F, and 20G to serial connectors 34A, 34B, 34C, 34D, 34E, 34F and 34G of the magazine 14A. These connectors 34A-34G respectively mate with serial bus connectors 36A-36G of the bay 20 (as part of connector structure 17 shown in Figures

1 and 2A). A set of Serial ATA Host controllers 38A-38G may be respectively connected to connectors 36A-36G. The controllers 38A-38G then connect to a SCSI target circuit 40, which connects via a suitable SCSI bus 42 to a SCSI host 50 within a host computing system. Each magazine 14 may be provided with a unique identifier, such as bar code pattern readable by a conventional bar code scanning system, and/or an electrical identifier such as an embedded serial number readable by the control circuitry 15 of a particular bay 20. Alternatively, each disk drive 20, or the magazine 14, or the bay 12, may include an internet protocol (IP) address in accordance with the internet data transfer protocol, TCP/IP. An optically readable identifier is preferably provided so that the identity of a particular magazine may be established during transit or storage and without need to plug the particular magazine 14 into a bay 12. The reader may be included as a part of the bay 12, or the reader may additionally or alternatively be a hand held unit of conventional design and function.

Power is most preferably supplied to each drive unit 20 in parallel from a high efficiency 48V to 5V/12V DC to DC switching converter circuit 44 located within the magazine 14A. The converter 44 derives its operating power through a magazine power connector 46 which mates with a bay power connector 48 connected to a DC power supply providing sufficient power to operate all seven of the drives 20 simultaneously. Drive operating power may be switched on at each drive unit 20 under software control from the host 50. Individual drive unit power switching is illustrated in Figure 3A by a power command register/switch circuit 49, there being seven such

circuits 49A, 49B, 49C, 49D, 49E, 49F, and 49G associated respectively with drive units 20A-20G.

Once archive data is written onto disk drive units 20 within a magazine 14 at an active storage system 100, the magazine 14 may be removed and reinstalled at a bay within a rack of the data preservation vault. Figure 3B illustrates a data preservation vault 300, which includes a drive monitoring system 304. The drive monitoring system 304 includes compatible data and power plug connectors, which mate with, like connectors of the magazine 14. In the example of Figure 3B, serial ATA connectors 318A, 318B, 318C, 318D, 318E, 318F, 318G mate respectively with connectors 34A-34G of magazine 14. A power connector 320 mates with power connector 46 of magazine 14. Since only one disk drive unit 20 will be powered at any time in the archive vault 300, the power connector 320 may have a smaller power handling capacity than the connector 48 of the active system 100. The drive monitoring system 304 includes a control line 322 for controlling a switch within the power connector 320 for selectively applying power to the DC to DC converter 44. Power to be applied to a particular drive is most preferably handled by drive unit commands sent from the drive monitoring system 304 to a particular drive unit 20 via the serial ATA bus structure.

Figure 4A illustrates an active data storage array 100A employing drive units in accordance with the USB 2.0 interface convention. A drive magazine 14E holds seven USB drives 20P, 20Q, 20R, 20S, 20T, 20U and 20V. The magazine 14E includes seven USB interface connectors 34P,

34Q, 34R, 34S, 34T, 34U, and 34V which respectively connect to drive units 20P-20V. The active unit 100A includes USB connectors 36P-36V which mate with magazine connectors 34P-34V, respectively. Seven USB host controllers 38P-38V are located between connectors 36 and the SCSI target 40. The SCSI target 40 connects to the SCSI host computing environment 50 via a high speed (2560Mb/second) bus 42.

Figure 4B illustrates a data preservation vault 300A for use with USB 2.0 magazine 14E. In this example, connectors 324P-324V mate with connectors 34P-34V and also to a USB hub circuit 326. The USB hub connects to a USB controller 328. The USB controller 328 connects too the drive monitoring system 304 via a lower speed bus structure 330 (operating in this example at 480 Mb/second). Otherwise, the Figure 4A-4B system is the same as the Figure 3A-3B system. Alternatively, each magazine 14 may include the USB hub 326 internally and provide a single USB connection to the SCSI target controller 114 for concentrating and distributing data from and to each drive unit 20, as shown in the Figure 8 arrangement, discussed below.

It is not necessary that the hard disk drive units be ATA or serial USB drives. For example, Figure 5 illustrates seven interface type 1394 hard disk drive units 20W, 20X, 20Y, 20Z, 20AA, 20BB, 20CC installed within an interface type 1394 magazine 14F. With the type 1394 interface convention, the interface bus of drives 20W-20CC may employ a single data bus 32W which is daisy-chained to all of the drive units and ultimately leads to a type 1394 magazine connector 34W arranged to mate with a bay

type 1394 connector 36W. While individual magazines 14 and magazine bays 12 may be provided for each interface type, a universal plug-jack interconnection system may be provided in accordance with known techniques, thereby to enable a magazine 14 to be used with disk drive sets of diverse interface conventions.

Figures 6A and 6B illustrate a shock mounting arrangement for use within the drive unit magazine 14. Therein, formed-foam shock absorbers 21 are placed between an outer frame of the magazine 14 and a bundle comprising the side-by-side mounted hard disk drive units 20. Each shock absorber 21 may be formed to define a series of nested rectangular spaces and openings adapted to fit closely over an outermost disk drive unit 20A or 20G, and provide an air passage to improve ventilation and cooling of the nested disk drive unit.

Turning now to Figure 7, a computing center active disk drive system 100 includes a multiplicity of hot-swap bays 12 of the type shown in Figures 1 and 2A, and associated HDD magazines 14, as shown in Figures 3A, 4A and/or 5. The system 100 is arranged in a series of large mounting racks 102, there being five such units 102A, 102B, 102C, 102D and 102E shown in the Figure 7 example. Dots to the right side of the rack 102E denote expandability of the system beyond the five racks shown in Figure 7. In addition to the interface subsystem 40 and host computer 50, the active system 100 may include a main board 102, an operator display 104, and a power supply 106, for controlling the magazines 14 and drives 20. The power supply 106 provides primary operating power to the main board 102,

controller 40, display 104 and each drive magazine 14 installed within the array of racks 102. As configured, the system 100 may provide active data backup as a full emulation of a tape library wherein each drive 20 emulates a separate tape cartridge. Alternatively, the active system 100 may provide
5 a primary random access data store for the host computer 50 and be configured in accordance with RAID or any other known storage system architecture and methodology.

Most preferably, the system 100 emulates a tape library system, such
10 as a tape library shown in commonly assigned U.S. Patent No. 5,925,119 to Maroney, entitled: "Computer Architecture for Automated Storage Library", the disclosure thereof being incorporated herein by reference. In a virtual tape emulation system 100, the main board 102 intercepts commands issued to a tape library system and converts tape-library-specific commands
15 such as media load/unload commands into electrical control signals for selecting/spinning up and down of a particular disk drive 20 and tape-file specific commands such as file read or write into logical block based disk-drive-specific commands by which logical block address locations are randomly accessed by the selected drive 20 so that a series of user data
20 block read or write operations are carried out on a tape file structured basis.

Figure 8 illustrates an embodiment 112 of the system 100 within an active computing environment which is configured to include a single SCSI target controller 114 for handling e.g. ten data unit magazines 14A, 14B,
25 14C, 14D, 14E, 14F, 14G, 14H, 14I, and 14J. The target controller 114 has a high bandwidth SCSI bus 118 leading to a SCSI host of the active

computer system (not shown in Figure 8). In this particular example, each magazine 14 is attached via a single SCSI port connector to the SCSI target controller 114, and each drive 20 within each magazine 14 has a SCSI interface.

5

Figure 10 shows one embodiment of a shock-providing carrying case 200 for transporting magazines 14 from the active computer center to the archive location. The case 200 includes a shock-resistant foam insert 202 that defines one or more wells, there being two wells 204A and 204B shown in the Figure 10 example. A lid 206 hinged to the case 200 and also having a shock-resistant foam sheet 208 secures magazines 14 placed in wells 204 against shock forces of the type typically encountered in removal to the archive location. A two-part latch mechanism 210A, 210B releasably secures the lid 206 to the case 200 in a closed position which causes facing walls of the foam insert 202 and lid sheet 208 to engage the magazines 14 and provide needed shock resistance for transport.

10

15

Figures 11 and 12 illustrate aspects of an archive system 300 that includes one or a series of side-by-side storage racks 302. The racks 302 may be located in any desired location, and most preferably in a secure archive location, such as a basement, vault, cave, or other location deemed to be secure against known hazards. The racks 302 may be grouped together, or they may be separated and located at otherwise unused areas of a computing center. Because the disk drives 20 in each magazine 14 are inactive for long periods of time, there is no need for level of power supply

20

25

or ventilation at the data preservation vault 300 that is needed for the racks 102 of the active backup system 100.

The drive monitoring system 304 includes a power supply 306 and connects to each magazine 14 installed in a particular rack 302 to supply power and a bus connection selectively to each drive 20 within a particular magazine 14, in order to carry out periodic testing and incidental archive data retrieval without requiring any operator intervention. The archive disk monitoring system controller 304 includes data inputs from an array 308 of environmental sensors, such as temperature, humidity, security access, etc. Most preferably, the archive system controller 304 includes a data path 310 extending to a remote operator console. The remote operator console enables the data vault 300 to be remotely accessed and monitored. Also, the channel 310 enables remote access to the archive information stored on one of the drives of one of the magazines of the system 300, should such real-time access be desired or required.

Figure 13 sets forth a flowchart of one exemplary disk drive monitoring routine 350 carried out by the data archive controller 304. At a step 352 the controller 304 applies power to one of the drives 20 within a particular magazine 14 in accordance with a master testing list maintained by and within the controller 304. The power is applied for a predetermined time period, such as three minutes or less, for example. At a step 354, the controller 304 sends a "run smart test" command to the drive under test. (The "run smart test" command is a host interface command within a superset of commands and enables a host computing system to test the disk

drive and receive status information. The disk drive undergoing testing provides status information back to the controller 304, such as its prognostics record. The controller 304 determines at the step 354 whether the drive undergoing testing passes or fails the smart test routine. If the drive presently being tested passes the smart test, the controller 304 ceases to apply power to the drive at a step 356. The next test interval for the particular drive passing the smart test is then recorded in the master testing list by the controller 304 at a step 358, and the testing procedure advances to a next drive on the testing list at a step 360, resulting in a return to step 352 and a repeat of the testing sequence is carried out for this next drive.

If, however, during the initial testing interval established by step 352, the disk drive undergoing testing fails to pass the smart test, disk drive 20Z for example, but still provides some functionality, as tested at a step 362, a stand-by archive drive 20R is located among the drives and the magazines of the rack 302, and the archive data on drive 20Z is transferred to the stand-by drive 20R during the step 352. Then, at a step 364 the controller 304 causes the panel lamp 22Z of the failed drive 20Z to flash in a manner indicating failure of the particular drive. At step 364 a message is also sent to the operator console to alert an attendant that an archive drive has failed and needs to be replaced within a particular magazine. The controller 304 then updates the archive records at a step 366 to reflect that the archive data once present on failed drive 20Z has been transferred to stand-by archive disk drive 20R.

If the failed drive 20Z loses all functionality, the controller 304 generates a message (step 368) based on its archive database to the host active system, indicating that the drive 20Z has completely failed. This message is most preferably sent via modem 308 and communications channel 310. The host computer may then be able to reconstitute the data lost on drive Z by resort to error correction techniques associated with data striping across multiple drives. In this regard, the host computer may request the archive system 300 to retrieve user data stripes and error correction overhead from other drives present within the array 300 and transmit that data in serial stream fashion to the host over channel 310. The host, then applying its error correction/recovery capability then reconstructs the data once held on drive z and sends that data over the channel 310 to a second stand-by drive 20RR, thereby completing the restoration of data within the archive array 300.

In one aspect of the present invention, each hard disk drive 20 may emulate a tape cartridge. In this aspect of the invention a disk drive will record "tape marks" or "file marks" which would normally be recorded onto tape by a tape drive. "File marks" represent overhead information (metadata) sent by the host to be written on tape to mark a boundary or partition, typically between files or volumes of user data information. In the present invention, file marks and other metadata intended to be recorded on a tape are actually written to a particular hard disk drive 20. One presently preferred arrangement is shown in Figure 14. Therein, a logical block address space 400 of a hard disk drive 20 is mapped to file space of a virtual tape media, including a beginning-of-media (BOM) mark 402, and an end-

of-media (EOM) mark 404. The BOM mark 402 corresponds to a logical block address zero (lba0), while the EOM mark 404 corresponds to a maximum logical block address (maxlba). Between the BOM mark 402 and EOM mark 404 are a series of file marks, four such file marks 406, 408, 410 and 412 being illustrated in the Figure 14 example. Each file mark 406, 408, 410 and 412 has a separate logical block address.

In use the host computer will issue a command that a master file mark be written to the media (which the host believes is tape, for example) The active system controller 106 causes the master file mark to be written outside of user logical block address space. On ATA disk drives 20 of the type discussed in connection with Figures 3A and 3B, the master file mark is written to one of 32 host-vendor-specific SMART log sectors. On SCSI/FibreChannel disk drives, of the type shown in Figure 5, the master file mark is written to the Client Application log page, for example. When a WRITE FILE MARK command is received by the main board 102, it will cause a selected drive to write a file mark structure at a current logical block address and update previous file mark data structures to include the address of the latest file mark just written. As shown in Figure 14, the file marks 406, 408, 410, 412, etc., are written across logical block address space in a linked manner most preferably comprising a double linked list heuristic. As shown in Figure 15, the file mark block structure is recorded in its own separate LBA sector of 512 bytes, for example. The file mark record structure includes a title field ("FILEMARK"), a major version field, a minor version field, a partition number, a byte of flag/validity bits, a

previous File Mark LBA, a next File Mark LBA, block size, reserved bytes, and two bytes of check sum, for example.

When the host computing system “loads” a virtual cartridge in the active backup system 100, a particular disk 20 drive is selected and reads the master file mark in its reserved space. It then traverses the file mark linked list and stores all file mark address locations in a file mark table of the active storage system’s volatile memory. When the selected disk drive receives a SPACE command to move to the next or previous number of file marks, the main board 102 retrieves the cache memory entry and moves the disk drive’s LBA pointer to the file mark location. When the active system main board 102 receives a READ or WRITE command, it will check the file mark cache memory to insure that the request does not cross a file mark boundary of the selected drive. If it does not, it will read or write the requested data file. If it does, then the active system main board 102 will issue a CHECK_CONDITION response to the host system.

In another alternative embodiment, a data preservation system is realized which embodies desirable characteristics of a RAID array with file access times less than 100 milliseconds and random data access, and also embodies desirable characteristics of a tape library which include ability to passivate a data volume by removing it from the drive thereby reducing both exposure and management costs while maintaining a relatively low demand upon electrical and thermal resources (because of the small number of active devices). With conventional hard disk drive interconnect architectures it has been extremely difficult to provide a system which has

the best characteristics of a random access RAID array and a tape library. Recent advances in storage networking offer new architectural alternatives. For example, if each hard disk drive of the array uses the TCP/IP internet protocol and employs an Ethernet-like physical transport technology, each
5 hard disk drive may be provided with a unique address and can be readily disconnected and powered down, and then powered up and reconnected to the network without disturbing other storage devices or elements of the network. The native network interface may be provided at the drive level, or it may be provided at the magazine level, or the bay level. In the present
10 example, the data protection system comprises a large number of high capacity (30 GByte to 100 GByte) hard disk drives, each drive having a direct network attachment and a unique network address.

A system controller controls the drives by providing power,
15 monitoring status, and providing redundancy (e.g. data striping or mirroring) as well as virtualizing the interface between the drives and the (e.g. user data backup) application. The system network then effectively supports simultaneous transfer of data to and from a large number of rotating hard disk drives. While any one of the many known network
20 connection arrangements are preferred, one particularly preferred example is several switched segments of Gigabyte Ethernet (GbE). In this approach, the computer support environment providing power and cooling is scaled to accommodate simultaneous operation of a small fraction, e.g. 5% to 10%, of the total array of disk drives simultaneously. The magazine approach
25 described hereinabove can be employed to facilitate swapping of hard disk

drives as well as removal and safe storage of hard disk drives containing archived user data.

Fundamental to the foregoing approach is the rotating hard disk drive unit itself. While any merchant market disk drive might be used, there are several characteristics that are highly desirable for disk drive units employed in the applications described herein. Among the most important disk drive characteristics are: a) a high confidence in data retention and integrity in an extended powered-off state; b) a native network interface; c) reliable, effective power cycling with minimum "drive ready" time latency from a powered-off condition; d) drive unit high data storage capacity and low cost per Gigabyte of user data stored; e) reliable initialization, control and monitoring for effective archive system management; and, f) convenient removal and replacement of disk drive units, and of magazines, to enable physical swap-out of drives, and removal and storage of drive magazines in an archive environment, most preferably of the type described hereinabove.

It will now be appreciated that the present invention provides protection of large user data files by employing disk drives in place of tape cartridges in a unique manner and configuration. The disk drives are most preferably arrayed within disk drive magazines. Each magazine holds a complement of high data capacity rotating hard disk drives which may emulate a like complement of tape cartridges. The disk drives may be initially employed in the active computing environment, and later on, after a nominal service life, the disk drives may be "retired" to provide the long-

term data archival functions described herein. Alternatively, new hard disk drives may initially be employed to provide the tape emulation/data archive functions of the systems described herein.

5 Having thus described several embodiments of the present invention, it will now be appreciated that the objects of the invention have been fully achieved, and it will be understood by those skilled in the art that many changes in construction and widely differing embodiments and applications of the invention will suggest themselves without departing from the spirit and scope of the invention. The disclosures and descriptions herein
10 presented are purely illustrative and are not intended to be in any sense limiting.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206